



葉興機械股份有限公司

YESSING MACHINERY CO., LTD.

www.yessing-machine.com.tw

E-mail:yessing@yessing.com.tw

No.21-5,Lane231,Gaomei Rd., Qingshuei District,  
Taichung City 43646Taiwan

43646台中市清水區高美路231巷21-5號

TEL:886-4-26265299 FAX:886-4-26268991



■ **LS-12B**

兩液型膠TPU膜貼合機

Two-Liquid Type Glue TPU Film Laminating Machine

**We can make its size and working width according to clients' demands.** ■■■■

可依客戶需求量身訂做尺寸及作業寬度 ■■■■

[機械尺寸] Machine Size (Approx.)

■ 約L 11630 x W 3216 x H 3150 mm

[使用寬度] Working Width

■ 1905mm (75")

[加熱裝置] Heat Device

■ 電熱式 Electric Heater

[電壓] Voltage

■ 依客戶需求配電 **Designed according to clients' demands**

[機台優點] Advantages

1. 具備高度精準的連動比。厚度0.015mm的薄膜，即使在高速作業下，仍不易拉伸。  
This machine has highly accurate linking rates. Even if working at high speed, the thin film only with the thickness of 0.015mm is still not easily stretched.
2. 由於兩液型的膠水初始含有溶劑，上膠後展開不易，經葉興研發出最完美的彩虹橋展開角度，即使在上膠後也能展開最平整的膜面，與布料進行貼合作業。  
Because Two-Liquid Type Glue contains dissolvent, the film is not easily spread after gluing. Through spreading rollers with the most perfect angle developed and researched by Yessing, the film can be easily spread even after gluing and laminated with fabric.

